



Resilience-based Earthquake Design Initiative (REDi) Rating System for the Next Generation of Buildings

SECED/EEFIT Meeting

April 30, 2014

Ibbi Almufti



Acknowledgments

Ron Alameida
San Francisco Dept. of Public Works

Prof. Mary Comerio
UC Berkeley

Damian Grant
Structural/Earthquake Engineer, Arup

Amit Khanna
Mechanical Engineer, Arup

Jason Krolicki
Structural/Earthquake Engineer, Arup

Sean Merrifield
Structural/Earthquake Engineer, Arup

Ken Paige
Building Owner

Tom Tobin
Tobin & Associates

Chuck Wright
Tishman Speyer

Prof. Jack Baker
Stanford University

Craig Davis
Los Angeles Dept. of Power and Water

Bob Hanson
Technical Leader for Mitigation, FEMA

Laurence Kornfield
Special Assistant to City of SF

Prof. Steve Mahin
UC Berkeley

Peter Morris
Davis Langdon

Andy Thompson
Risk Consultant, Arup

Prof. Andrew Whittaker
SUNY Buffalo

Michael Bade
Assistant Vice Chancellor UC San Francisco

Prof. Gregory Deierlein
Stanford University

Michael Delucchi
Trans Pacific National Bank

Russ Drinker
HOK

Prof. Leonardo Duenas-Osorio
Rice University

David Friedman
Forell/Elsesser Engineers

Audrey Galo
Architecture for Humanity

Stuart Inglis
Risk Consultant, Arup

Laurie Johnson
Laurie Johnson Consulting

Mary Kasaris
First Republic Bank

Shaun Landman
Electrical Engineer, Arup

Renee Lee
Risk Management Solutions

Andrew Lusardi
Turner Construction

Lindsey Maclise
Forell/Elsesser Engineers

Stephen McLandrich
Geotechnical Engineer, Arup

Prof. Eduardo Miranda
Stanford University

Prof. Judith Mitrani Reiser
Johns Hopkins University

Prof. Ramin Motamed
University of Nevada, Reno

Gregory Nielsen
Structural/Earthquake Engineer, Arup

Nick O'Riordan
Geotechnical Engineer, Arup

Katherine Shelton
First Republic Bank

Michael Steiner
Architecture for Humanity

Jenni Tipler
Stanford University

Alex Wilson
Resilient Design Institute

Deborah Wylie
Associate Vice President UC

Troy Zezula
Facades Consultant, Arup

*SEAONC Building Ratings
Committee:*

Marguerite Bello

Mathew Bittleston

Stephen Bono

David Bonowitz

Ron Mayes

Dave McCormick

Evan Reis

Kate Stillwell



Our challenge

“the true costs of a disaster are **felt most acutely at community level**”





Modern Building Codes – “Life Safety” Objective


Code protects lives –
does *not* limit damage
or maintain
functionality






© PETER YANEV

Consequences of code design






Performance Expectation for RC Tall Buildings in San Francisco



Performance Expectation for RC Tall Buildings in San Francisco



Loss drivers

2.5 years to achieve functional recovery after a big earthquake

\$47M to repair the building (~26% of building value)

Central Business District
was closed for more than
2 years.



Royal Commission Reports



H.2



H.2




H.2




FINAL REPORT

VOLUME 1
SUMMARY AND RECOMMENDATIONS IN VOLUMES 1-3
SEISMICITY, SOILS AND THE SEISMIC DESIGN OF BUILDINGS



FINAL REPORT

VOLUME 2
THE PERFORMANCE OF CHRISTCHURCH CBD BUILDINGS



FINAL REPORT

VOLUME 3
LOW-DAMAGE BUILDING TECHNOLOGIES



Royal Commission Conclusions

- *“...it would not be sensible, in our opinion, to conclude that the performance of buildings in the February earthquake demonstrates a need for wholesale change.”*
- *“...the objective should be incremental improvement, rather than a change of direction, and the necessary improvements can be incorporated within the framework of the present rules.”*
- *“However, once the objective of life-safety is achieved, the question of the extent to which buildings should be designed to avoid damage is a social and economic one, and the answer depends on choices that society as a whole must make.”*
- *“In the circumstances, our concept of “best practice” is one that reflects the existing objective of life-safety, and looks to ensure that building damage is minimized within the limits established by the existing knowledge about earthquake risk and our understanding of the cost implications of more onerous requirements.”*
- *“Any other approach would be a radical change that we do not consider would be justified by the experience of the Canterbury earthquakes.”*

•



Other consequences – loss of culture, sense of community, and quality of life




Design to resume business operations and provide livable conditions quickly after an earthquake



© FONG & CHAN




REDi™ Rating System




A **framework** to implement “**resilience-based earthquake design**” for achieving ‘*beyond-code*’ resilience objectives.

REDi Resilience Objectives






Defining Post-Earthquake Recovery States






Paths to Re-occupancy and Functional Recovery if Building Undamaged




Paths to Re-occupancy and Functional Recovery if Building Damaged





REDi Roadmap to Resilience





Guiding Principles

Platinum

- * Enhance design of structure and architectural components such that the building and contents suffer only minimal (aesthetic) damage.
- * Provide “beyond-code” provisions for egress systems and other improvements to occupant safety
- * Protect MEP components and other critical systems. Provide back-up systems. This enables continued operations of primary functions in the absence of utilities.
- * Pre-identify contingency plans to provide water and fuel and waste removal or employ alternative off-grid technologies in the event of extended utility disruption.
- * Minimize risk of generally uncontrollable externalities which may affect functionality, including site access restrictions and potential damage from external hazards such as surrounding buildings.


Gold

- * Enhance design of structure and architectural components such that the building and contents suffer only minimal (aesthetic) damage .
- * Provide “beyond-code” provisions for egress systems and other improvements to occupant safety
- * Protect MEP components and other critical systems or guarantee that they are replaced/repared within 1 month. This enables normal operations to resume once utilities are restored

Silver



- * Damage to the building may potentially result in a “Yellow Tag” which would prevent re-occupancy until the building is repaired.
- * Provide “beyond-code” provisions for egress systems and other improvements to occupant safety
- * A skilled contractor is required to make repairs to restore the building to a state which can support functional recovery within 6 months. It may be necessary to mitigate “impeding factors” (see Glossary of Terms) to meet this downtime objective.
- * The building can resume normal operations only once the building is repaired and utilities are restored.

FEMA-based Earthquake Loss Assessment




Performance-based Seismic Analysis

D3PLOT: Nonlinear BRB's - Liquefaction





Fragility Curves



Partitions


DS1:
Cracking

DS2:
Crushing


DS3:
Warping
of studs



Consequence Functions



Confidence Levels for Earthquake Losses






Improvement of FEMA Method for Downtime

1. Definition of “Repair Classes”
2. Estimates of delays due to “Impeding Factors”
3. Estimates of utility restoration times
4. Sequential logic for calculating the time to achieve re-occupancy, functional recovery, and/or full recovery.

“Repair Classes”

- Purpose to determine whether damage to specific components will hinder a specific recovery state
- Maps FEMA Damage States for each component into “Repair Classes”
- Depends on criticality of component and extent of damage



Impeding Factors to Recovery




Figure 12. Impeding curve for post-earthquake inspection

Impeding Factors to Recovery




Figure 14. Impeding curves for financing repairs

Utility Restoration Curves





Figure 19. Utility disruption functions - electrical (top), water (middle), gas (bottom)

Site-specific Utility Restoration Curves for SF



Laurie Johnson PhD AICP Consulting | Research

Performance Expectation for REDi-designed Tall Buildings in SF

- \$5.8M to repair *cosmetic* damage
(~3.5% of building value)
- Immediate re-occupancy
- Functionality is achieved within
1 month





Performance Expectation for REDi-designed Tall Buildings in SF

How?

- \$5.8M to repair *cosmetic* damage (~3.5% of building value)
- Immediate re-occupancy
- Functionality is achieved within *1 month*

- Innovative structural system
- Enhanced partition connections
- More displacement-tolerant façade system
- Stronger elevator guiderails
- MEP equipment functioning
- Contingency plans



But that must cost a fortune!?

REDi building costs *only 2%* more than the conventionally designed building



Potential Incentives

Increased rental premiums for resilient buildings – approximately **5% to 10%**

免震建物 入居者アンケート

2006年12月、当社施工の免震物件において、入居者の皆様にアンケートを実施致しました。

免震効果で賃料UP!
平均¥5,576(4.8%)UP!

●免震物件入居者向けアンケートの実施要領

- 【時期】 2006年12月5日(火)発送
- 【対象】 2006年12月15日(金)回答期限
- 【対象】 竣工した直後の免震物件(全2棟264世帯)に送付
- 【内容】 119世帯より回答あり(回答率45.0%)
- 【用途】 アンケート用紙・免震概要説明資料
- 【内容】 免震マンションの入居者に向け、地震に対する不安や免震に対する認知度や満足度を調査

免震マンションの賃料について

質問内容...


「条件が同じであれば、免震でない一般のマンションと比較したとき、いくら賃料(1カ月)の差までなら免震マンションを選びますか?」

回答内容...

「1,000円～5,000円」の回答が多く、全体の半数を超えています。「20,000円」以上も許容できるとの回答もあり、**免震が賃料アップ効果に繋がっている**ことが分かります。

また、各回答の中間値(例えば、「1,000円以上～3,000円未満」との回答の場合は「2,000円」)を希望金額とすると、全体の平均を取ると、「5,576円」となりました。

Q11. 条件が同じであれば、免震でない一般のマンションと比較したとき、いくら賃料(1カ月の差)までなら免震マンションを選びますか?



各免震物件の許容できる賃料と許容率

各免震物件に対して、許容できる賃料を「許容率」として、下記の通りまとめました。全体の平均では現状の賃料に対して**免震であれば4.8%の賃料アップでも良い**との回答になっています。特に、間取りが広く、賃料も高い「免震物件F」においては、平均で「11,318円ものプラス」になっています。

物件名	賃料	間取り	駅徒歩	許容賃料	許容率
免震物件A	105,000円～146,000円	1SLDK-2LDK	15	¥3,692	2.9%
免震物件B	98,000円～149,000円	1LDK～3LDK	3	¥6,595	5.0%
免震物件C	102,000円～115,000円	1LDK～2LDK	17	¥4,938	4.2%
免震物件D	72,000円～139,000円	1K～2LDK	7	¥4,310	4.3%
免震物件E	74,000円～140,000円	1K～2LDK	7	¥6,250	5.3%
免震物件F	162,000円～180,000円	2LDK～3LDK	4	¥11,318	6.2%
免震物件G	69,000円～79,000円	1K	5	¥4,409	5.5%
免震物件H	71,000円～105,000円	1K～2K	1	¥4,500	5.2%

※許容賃料 ÷ 現状の賃料 = 「許容率」



PACIFIC EARTHQUAKE ENGINEERING RESEARCH CENTER

Seismic Performance Objectives for Tall Buildings

A Report for the Tall Buildings Initiative

William T. Holmes
Rutherford & Chekene

Charles Kircher
Kircher & Associates

William Petak
University of Southern California

Nabih Youssef
Nabih Youssef Associates

PEER 2008/101
AUGUST 2008



Potential Incentives


- **Governments:** zoning flexibility, expedited permits, etc
- **Insurers:** reduced premiums and capacity



Project Example



- Downtown SF
- 55 stories, 800' tall
- Mixed-use

Earthquake Hazard in SF Bay Area



Tall Building Performance-based Design Guidelines (PEER TBI)

- SF required for most tall buildings
- Requires code-equivalent performance (i.e. “life-safety” and “collapse prevention”)




PREPARED FOR
City of San Francisco Department of Building Inspection

PREPARED BY
Structural Engineers Association of Northern California (SEA/NC)
AS-083 Tall Buildings Task Group
Joe Maffei, S.E., Ph.D. (Chair)
Michael Gemma, S.E.
Ronald Hamburger, S.E.
Neddie Mathias, S.E.
Jack Moonile, PE, Ph.D.
Aron Moore, S.E. (Chair, SEA/NC Seismology)
Jeffrey Tomer, S.E. (Chair, SEA/NC Professional Practices)
Marko Scholten, Ph.D. (Chair's Assistant, non-voting)

APPROVED BY
SEA/NC Board of Directors
Doug Holboach, S.E. (President)
William Andrews, S.E.
Grace Kong, S.E.
Peter Lee, S.E.
Ben Litzrand, S.E.
Andrew Meronch, S.E.
Gary Modrak, S.E.
David Murphy, S.E.
Peter Revelt, S.E.

First REDi “Gold” Building



- Owner (developer) wants to pursue REDi “Gold” objectives
- Incorporated into Basis of Design

1.1.1 - Resilience Workshop

Conduct a comprehensive workshop with the Owner...to agree on resilience objectives and to identify risk drivers and a resilience plan for the facility...




Structural Design

2.2.4 - Minimize Structural Damage

The superstructure (and foundations) are designed to remain essentially elastic (e.g. cracking allowed) for the demands in 2.2.2

Reduced Earthquake Demands



Non-structural Enhancements

2.3.1 - Minimize Non-structural Damage

For non-structural components... design the anchorage to remain essentially elastic and design the components to accommodate relative displacements with minimal (aesthetic only) damage.






Figure 2.1. Cross section (on the left) and side-view elevation (on the right) of the proposed new sliding/frictional connection.

Improved Partition Connection Performance


Standard
Partition



Improved
Partition



Viable Alternative?



(a) Friction Connection (Slip Track)




(b) Friction Connection: corner

Functional MEP Systems

2.3.2 - Equipment Functionality


Mechanical and electrical equipment, back-up systems, or any other mission-critical components...to remain operable in the design level earthquake.



Façades

2.3.4 Protect Facades

Façades and curtain walls are designed and tested to accommodate relative displacements such that connections remain elastic and the building envelope remains effective in preventing air and water intrusion.



Elevators

2.5.3 - Elevators

Elevator design meets the California Office of Statewide Health Planning and Development (OSHPD)...



Expected Cost Implications to Achieve REDi Gold

Enhancement	Cost above Baseline
Essentially elastic structure using innovative seismic features	None
Enhanced partition connections	~5% premium
Displacement-tolerant façade system	None
Stronger elevator guiderails to meet CA hospital requirements	\$63k to upgrade S1
Seismically-certified MEP equipment	?
Essentially elastic component anchorage	Nominal
Contingency planning: <ul style="list-style-type: none"> - Retain professional for post-EQ inspection - Train facility manager to certify elevator 	\$15k/yr
Recommendations for tenant fit-out contracts: <ul style="list-style-type: none"> - Anchor heavy and mission-critical contents - Improved partitions - Food and water 	None
Observation of non-structural component installation	\$50k
Seismic Peer Review	None



Lessons (being) learned

- People comfortable with the status quo
- Some cost premium OK
- All design team members are key – especially the architect
- Supportive and willing owner
- The prospect of reduced earthquake insurance premium is a driver



REDi Guidelines available for download

www.arup.com/publications

